

Thông số kỹ thuật

M series 1.5t Power Stacker specification						
General	1	Model			PSB15-MC	
	2	Power Type			Electric	
	3	Type of operation			Pedestrian	
	4	Rated Capacity		Q(kg)	1500	
	5	Load Centre		C(mm)	600	
speciality and size	6	Lift height			h3(mm)	2900
	7	Free Lift Height			h2(mm)	150
	8	Lowered mast height			h13(mm)	85
	9	Height of tiller in drive position min./max.			h14(mm)	1030/1305
	10	Fork overhang (Wheel center to fork face)			X(mm)	785
	11	Ground clearance(Bottom of mast)			m2(mm)	25
	12	Overall demensions	Length to face of fork(With fork)		l1(mm)	2008
	13		Length to face of fork(Without fork)		l2(mm)	858
	14		Overall width		b1(mm)	795
	15		Mast lowered height		h1(mm)	1955
	16		Extended mast height		h4(mm)	3230
	17	Fork size		LxWxT	s/e/l(mm)	60x180x1150
	18	Width over forks			b5(mm)	575
	19	Aisle width for pallets 1000x1200 crossways			Ast1(mm)	2224
	20	Aisle width for pallets 800x1200 lengthways			Ast2(mm)	2271
21	Turning radius			mm	1690	
Performance	21	Speed	Travel	laden/unaden	km/h	5/5.5
	22		Lifting	laden/unaden	mm/s	134/212
	23		Lowering	laden/unaden	mm/s	123/130
	24	Max.Gradeability		laden/unaden	%	6/12
	25	Service brake				Electromagnetic
Chassis	26	Types			Polyurethane	
	27	Types demensions	Driving type		Φ230x75	
	28		Rear		Φ80x70	
	29		Front		Φ124x60	
	30	Number	X=driving wheel (Front/Rear)		1X+2/4	
	31	Tread	Front		b10(mm)	570
	32		Rear		b11(mm)	395
Weight	33	Wheelbase			Y(mm)	1367
	34	Self weight			kg	1028
	35	Axle loading	Full Load	Front/Rear	kg	1130/1395
	36		No Load	Front/Rear	kg	700/325
Driver	37	Drive motor rating			kw	1.5
	38	Lift motor rating			kw	3
	39	Battey	Voltage/Capacity		V/Ah	24/210
	40		BS standard			3VBS
Others	41	Type of drive control				Mosfet Control
	42	Sound levelat driver's ear acc. to EN12053			dB(A)	67